



19" Contactless Touch Display CM-PO190I

Put customers at ease and encourage usage with a safe, non-touch for your interactive kiosk. The CM-PO190I utilizes infrared technology to provide a simple and intuitive way to interact with a kiosk without physically contacting the surface of the touch display. The touch interface provides users a positive user experience by offering responsive and precise input control. Perfect for high-traffic areas, the CM-PO190I helps to improve public safety by reducing the spread of infectious diseases and contamination. The CM-PO190I provides a seamless and safe user experience across various vertical markets and applications in wayfinding, visual communications, and informational and other interactive kiosk applications.

- Contactless Touch with USB Interface
- 1000:1 Contrast
- 450 Nits Brightness

- Responsive and Precise Input Control
- Simple, Intuitive User Interface
- 1280 x 1024 SXGA Resolution

Specifications

Display

Model CM-PO190I

LCD

19" TFT LCD Size/Type

Panel Ratio 5:4

Max.

1280 x 1024 Resolution

Typ. **Brightness** 450 nits (LCD brightness) 400 nits (after protection

glass)

Contrast Ratio

1000:1

Backlight

WLED

Backlight Life

50,000 hours

Display Colors

16.7 M

Viewing

Angle

170/160 (H/V)

Response

Time

10 ms (Tr + Tf)

Touch

Touch Type Infrared

Multi-Touch 2 Point **Input Method** Contactless

Interface **USB**

OS Support Windows 10 IoT

Power Requirements

Power Input 12V DC

Power

Consumption < 27 W

(Typ.)

AC to DC, DC 12V 3A, **Power Adapter**

36W Adapter

Interface

HDMI x1 **VGA** х1

USB x1

DC Power DC Jack

Audio 2W x2 (optional)

Physical Properties

Dimensions 441.2 x 366.2 x 78.09 mm (WxDxH)

Net Weight 4.5 Kg

VESA Mount (100 x 100) Mounting

Chassis Color Black

Environment

Operating Temperature

0 to 50 °C

Storage

Temperature

-20 to 60 °C

Regulatory Certifications

FCC EMC & Safety


Post-Production Support


Warranty 1-Year Standard

> Extended warranty options available

^{*} Specification subject to change without notice. Updated March 12, 2020

Mechanical Drawing







Ordering Information

Part Number	Description
CM-PO190I45SX	19 inch 450 nits, 1280 x 1024, Contactless Touch Display
Packing List	

19" Contactless touch monitor, adaptor cable, power cable, USB-B cable, DVI cable, HDMI cable, VGA cable.

Buy Online (U.S. Customer Only): www.ContecAmericas.com

Contec Americas Inc.

3991 Sarno Rd. Melbourne, FL 32934

Toll Free: (888) 285-0172 Local: (321) 728-0172 Email: sales@us.contec.com Global Website: www.Contec.com

