



* Specifications, color and design of the products are subject to change without notice.

Features

Opto-coupler isolated input (supporting current sink output and current source output)

Equipped with opto-coupler isolated input 16ch (supporting current sink output and current source output) whose response speed is 1msec. Common terminal provided per 16ch, capable of supporting a different external power supply Supporting driver voltages of 12 - 24VDC for input and 12 - 48VDC for output

Conforming to the USB1.1 and USB2.0 Standards and supporting the internal and external power supplies

Compatible to USB1.1/USB2.0 and capable to achieve high speed transfer at HighSpeed (480 Mbps).

Not necessary to power this product externally as the bus power of USB is used. Capable of accepting an external power supply (optional AC adapter) when lower power consumption is required, e.g., for use with a notebook PC

Opto-coupler bus isolation

As the USB (PC) is isolated from the input interfaces by opto-couplers, this product has excellent noise performance.

Trigger monitor function integrated

The CPU inside the module can report status changes (rise and fall) to the host in a minimum cycle of 1ms.

Easy to increase the number of input channels using an expansion module

Adding optional modules (up to 3 units) can easily increase the number of input channels.

The unique structure for connection by stacking enables easy and compact system configuration.

Screw-less connector plug facilitating wiring and plugging/unplugging

Wiring and plugging/unplugging are easy as the screw-less connector plug is used.

Capable of being mounted on 35-mm DIN rails

The module is equipped with an attachment for mounting on 35-mm DIN rails on the back, allowing the module to be attached onto and detached from DIN rails.

LabVIEW is supported by a plug-in of dedicated library VI-DAQ.

Using the dedicated library VI-DAQ makes it possible to create each application for LabVIEW.

This product is a USB 2.0 compliant module that extends the digital signal input functions of a PC.

This product is a 12 - 24VDC opto-coupler isolated type with input 32ch.

Using the expansion module available as an option can increase the number of input channels. In addition, this product has an attachment that allows this product to be directly attached onto 35-mm DIN rails useful for embedded applications. Windows driver is bundled with this product. Possible to be used as a data recording device for LabVIEW, with dedicated libraries.

Product Specification

Hardware Specification

Item	Specification		
Input section			
Input format	opto-isolated input Compatible with current sink output: negative logic *1, Compatible with current source output: positive logic *2		
Number of input signal points	32 points (32 points/common)		
Input resister	3kΩ		
Input ON current	3.4mA(Min.)		
Input OFF current	0.16mA(Max.)		
Response time	1msec(Min.) *3		
External power	12 - 24VDC (±15%) (per point 4mA/12V - 8mA/24V)		
Allowable distance of signal extension	Approx. 50m (depending on wiring environment)		
Communication			
USB transmission speed	12Mbps (full speed), 480Mbps (high speed) *3		
Current consumption	+5VDC 450mA(Max.)		
Others			
Number of modules used at the same time	127 modules (Max.) *4		
Use condition*5	0 - 50°C 10 - 90%RH (no condensation)		
Physical dimensions (mm)	$50.4(W) \ge 64.7(D) \ge 94.0(H)$ (exclusive of protrusions)		
Weight of the module itself	160g		
Module installation method One-touch connection to 35mm DIN rails (standard connection mechanism provi system)			
Expansion module	DI-32(FIT)GY: 3 modules (Max.) consumption current per module: +5VDC 150mA (Max.)		
Compatible plug	FMC1,5/18-ST-3.5 (made by Phoenix Contact corp.) 3.5mm-pitch nominal current: 6A (Max.)		
Compatible wires	AWG24 - 16		

1 Data"0" corresponds to high-level and data"1"corresponds to low-level. 2 Data"1"corresponds to high-level and data"0" corresponds to low-level.

*3 USB module executes API function by USB communication. The executing time of API function by

USB communication is about several msec in practice (Depending on the contents handled by API function, it may be longer than that). The responding speed of USB module is based on the environment of the host PC being used.

*4 The USB interface can accommodate up to 127 devices on the bus. As a USB hub itself is counted as one device, however, 127 USB modules cannot be connected.

*5 When using the attached AC adaptor POA200-20-2, it is 0 - 40° C

Software Specification

Item	Specification		
Support OS	Microsoft Windows 98 or Second Edition Microsoft Windows Me Microsoft Windows XP Professional, Home Edition Microsoft Windows 2000 Professional Microsoft Windows Vista Microsoft Windows Server 2008 Microsoft Windows 7		
Support language	Microsoft Visual C++ Ver 5.0, Ver 6.0 Microsoft Visual C++ .NET 2002, 2003 Microsoft Visual Basic Ver 5.0, Ver 6.0 Microsoft Visual Basic .NET 2002, 2003 Microsoft Visual C# .NET 2002, 2003 Borland Delphi Ver 5.0, 6.0 Borland C++ Builder Ver 5.0		
System requirement	 PC (IBM PC/AT compatibility, DOS/V) with USB port CD-ROM drive Recommend the environment on which the using language can run smoothly 		

Support Software

Driver Library API-USBP(WDM) (Bundled)

It is the library software, and which supplies command of hardware produced by our company in the form of standard Win32 API function(DLL). Using programming languages supporting Win32API functions, such as Visual Basic and Visual C++ etc., you can develop high-speed application software with feature of hardware produced by our company. In addition, you can verify the operation of hardware using Diagnostic programs.

CONTEC provides download services (at

http://www.contec.com/apiusbp/) to supply the updated drivers and differential files.

Further details may be found in the help within supplied CD-ROM or the homepage of our company.

< Operating environment >

os	Windows 7, Server 2008, Vista, XP, Server 2003, 2000, Me, 98			
Adaptation language	Visual Basic, Visual C++, Visual C#, Delphi, C++ Builder			

Accessories

Accessories (Option)

Isolated input module (Expansion module)	: DI-32(FIT)GY
AC adapter (input: 90 - 264VAC, output : 5VDC 2.0A)	: POA200-20-2
AC-DC power supply unit (input: 85 - 132VAC, output: 5VDC 3.0A)	: POW-AC13GY
AC-DC power supply unit (input: 85 - 264VAC, output: 5VDC 2.0A)	: POW-AD22GY
DC-DC power supply unit (input: 10 - 30VDC, output: 5VDC 3.0A)	: POW-DD10GY
DC-DC power supply unit (input: 30 - 50VDC, output: 5VDC 3.0A)	: POW-DD43GY
* Further details of the accessories may be verified in the W	eb site of our company.

Packing List

USB module [DI-32(USB)] ...1 First step guide ... 1 CD-ROM *1 [API-USBP(WDM)]...1 Interface connector (plugs) FMC1,5/18-ST-3.5...2 Power connector MC1,5/3-ST-3,5 ...1 USB cable (1.8m)...1 Rubber feet...4 Magnet...2

*1 The CD-ROM contains the driver software and User's Guide.

Block Diagram



Points

The Device ID is fixed at "0".

Physical Dimensions



Signal Layout

For connection of this module to an external device, use a pair of 18-pin connectors on the module.

P N	in o.	Signal name	Meaning		Pin No.	Signal name	Meaning
	Х				Х		
C	C0	СОМ	Common for Input+0, +1 group		C1	СОМ	Common for Input+2, +3 group
Ν	١C	N.C.	Unconnected		NC	N.C.	Unconnected
(00	IN00			20	IN20	
(01	IN01			21	IN21	
(02	IN02			22	IN22	
(03	IN03	Input+0 aroup		23	IN23	Input+2 group
(04	IN04	input o group		24	IN24	inputiz group
(05	IN05			25	IN25	
(06	IN06			26	IN26	
(07	IN07			27	IN27	
	10	IN10			30	IN30	
	11	IN11			31	IN31	
	12	IN12			32	IN32	
	13	IN13	Input+1 group	Q Q 15 35	33	IN33	Input+3 group
	14	IN14	input+i group		34	IN34	input+5 group
	15	IN15			35	IN35	
1	16	IN16			36	IN36	
	17	IN17			37	IN37	

Connection Method

When connecting the Module to an external device, you can use the supplied connector plug. When wiring the Module, strip off approximately 9 - 10 mm of the covering for the cable, and insert the bare wire by pressing the orange button on the connector plug. Releasing the orange button after the wire is inserted fixes the cable. Compatible wires are AWG 24 - 16.

▲ CAUTION

Removing the connector plug by grasping the cable can break the wire.



External Input Circuit

Input Section

Figure below shows the input equivalent circuit for the interface section.

The signal input section consists of an opto-isolated input (compatible with both current sink output and current source output). Therefore, driving the input section for the Module requires an external power supply with a minimum capacity of approximately 8mA (or 4mA for 12VDC) per input point for 24VDC.

Input Circuit



Example of a Connection to Current Sink Output



Example of a Connection to Current Source Output



Connecting an External Power Supply

The module can be used via only USB cable if it uses bus power. In this situation, the external power supply is not required.

If you want to control the power consumption of the computer with battery, such as Note PC, you can use self-power to provide power for the module. In addition, if you use expansion modules, the self-power is required. When you use self-power, please use +5VDC input terminal.



Input plug is 5VDC ±5% input, Laterally operable screw-in type connector is supplied as a standard item. (MC1,5/3-ST-3,5 Phoenix Contact compatible cable:AWG28 - 16) To supply power using the bundled connector plug (MC1,5/3-ST-3,5), strip the end of the corresponding cable, insert it into the connector plug, then securely screw the plug.

Use an external power supply (available as an option) depending on the operating environment and application.

Category	Model	Input	Output	Physical dimensions(mm)	DIN rail
AC	POA200-20-2	90 - 264VAC	5.0VDC±5%	47.5(W) x 75(D) x 27.3(H)	No
adapter			2.0A(Max.)	(exclusive of protrusions)	
AC-DC	POW-AD13GY	85 - 132VAC	5.0VDC±5%	52.4(W)x64.7(D)x94.0(H)	Yes
power			3.0A(Max.)	(exclusive of protrusions)	
AC-DC	POW-AD22GY	85 - 265VAC	5.0VDC±5%	52.4(W)x64.7(D)x94.0(H)	Yes
power			2.0A(Max.)	(exclusive of protrusions)	
DC-DC	POW-DD10GY	10 - 30VDC	5.0VDC±5%	25.2(W)x64.7(D)x94.0(H)	Yes
power			3.0A(Max.)	(exclusive of protrusions)	
DC-DC	POW-DD43GY	30 - 50VDC	5.0VDC±5%	25.2(W)x64.7(D)x94.0(H)	Yes
power			3.0A(Max.)	(exclusive of protrusions)	
* The concurrent of DL 22(LISP) is LEV/DC 450mA(Max) individually					

The consumed current of DI-32(USB) is +5VDC 450mA(Max.) individually. The consumed current of DI-32(FIT)GY is +5VDC 150mA(Max.) individually.



When using the power supply installable on DIN rail, please use the connector MC1,5/3-ST-3,5 (Phoenix Contact).

Connecting method

To connect the external power supply and USB cable to the unit, take the steps below:

- (1) Connect the external power connector to supply power for the USB module.
- (2) Connect the USB module with computer using USB cable.

To remove the external power supply and USB cable from the unit, take the steps below:

- (1) Remove USB cable.
- (2) Remove external power connector, stop power supplying to the USB module.

A CAUTION

To use the AC adapter, connect it to the USB module first, then plug the AC adapter's connector into a wall outlet.

When the USB module is not used, leave the AC adapter unplugged

Continuously using the AC adapter heated affects its life.

Use the AC adapter not in a closed place but in a well-ventilated place not to be heated. The AC adapter heats up itself when loaded heavily. If the AC adapter is exposed to high temperature or used continuously, you should keep the load at about 80% of the maximum load (at 1.6 A for the POA200-20-2).

Connecting with Expansion Accessories

When lacking of digital I/O point used to connecting external device, you have to purchase a new same module, and thus it not only increases cost but also doubles installation space. As this module is designed considering the growth in the number of I/O channels, the connectors on the side face can accept additional modules to save the cost and installation space for expansion.

Expansion modules (options) are available to each type of USB module.

Model	Input point	Output	Current	Function
		channel	consumption	
DIO-16/16(FIT)GY	16	16	+5VDC	Expansion module for
			150mA(Max.)	DIO-16/16(USB)
DI-32(FIT)GY	32	None	+5VDC	Expansion module for DI-32(USB)
			150mA(Max.)	
DO-32 (FIT)GY	None	32	+5VDC	Expansion module for
			150mA(Max.)	DO-32(USB)

Up to three expansion modules can be connected. For example, the combination of the USB module "DIO-16/16(USB)" and three expansion modules "DIO-16/16(FIT)GY" can be used to control up to 64 inputs and

64 outputs through a single USB port.



Points

Up to 3 modules can be connected.

Adding an expansion module requires an external power supply such as the AC adapter (option).

Modules functionally incompatible with the USB module cannot be connected. Use dedicated modules.